

THE BEST & LAST ROOF COATING YOU'LL EVER USE!

Low VOC
GacoRoof



GACOROOF IS IDEAL FOR:

- Aged Asphalt*
- Aged EPDM and TPO/CPA*
- Built-Up
- Cap Sheet
- Composite
- Concrete
- Fiberglass
- Metal
- Modified Bitumen
- Torchdown
- Sprayed Polyurethane Foam
- Most Existing Coatings
- Low-Pitched Roofs
- Flat Roofs
- Mobile Homes
- RVs & Campers

*Not for use on 3-tab asphalt or architectural shingles.
* May require GacoFlex E5320 2-Part Epoxy Primer/Filler.
Verify adhesion with a GacoRoof AdhesionTestKit.
Low VOC available.

WHITE
GR1600C

GRAY
GR1628C

LIGHT TAN*

Note: Colors shown are printed representations of product color. Actual color may vary slightly due to surface texture, application technique and lighting conditions.

*Requires the use of GacoRoof Colorant - Mojave Tan

FLIP OVER TO COMPARE FOR YOURSELF...

GACOROOF.COM 866 422 6489

GacoFlex[®]
by Gaco Western[®]

COMPARE FOR YOURSELF



	GACOROOF	Brand X
Warranty	LIMITED 50-YEAR	5-10 Years
Can be applied between 32° - 120°	YES	NO
Withstands Permanent Ponding Water	YES	NO
Primer/ Basecoat Required?	NO*	YES
Re-coating Required?	NO	YES

- **2 coat application of same product**
Brand X requires multiple products
- **Withstands permanent ponding water**
Brand X is 48 hours only
- **Temperature application range 32°-120° F**
Brand X is 50°-90° F
- **1-12 hour cure time, dry to the touch**
Brand X is 24-48 hours
- **1 gallon = 100 sq. ft. per coat**
Brand X is 1.5 gallons
- **Can be used on flat roofs**
Brand X requires 1/4" slope
- **Can be rained on after 2 hours**
Brand X requires no rain, dew or fog within 24-48 hours
- **Permanently flexible**
Brand X becomes brittle and begins to degrade over time
- **Recoat can be done after cure time**
Brand X may require 24 hours before re-coat
- **Silicone Roof Coating**
Brand X sells all acrylic roof coatings
- **Ponding waterproof**
Brand X is ponding water resistant
- **50 year warranty**
Brand X 5-10 year warranty
- **No polyester mat between coats**
Brand X requires polyester mat
- **UV resistant**
Brand X loses mil thickness due to UV exposure
- **22 mil system**
Brand X is 48-60 mil

GACOROOF.COM 866 422 6489

GacoFlex
by Gaco Western®