

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: ADOBE AROMATIC URETHANE - POLYOL COMPONENT A
Product Code: U6618P, U6618P-1, U6618P-5, U6618P-Q

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Architectural Coating and Waterproofing
 Use this product in accordance with all local, regional, national and international regulations.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Gaco Western LLC
 1245 Chapman Dr.
 Waukesha, WI, 53186-5942
 USA
Telephone Number: 800-331-0196 / **International:** 001-800-331-0196
Email: sds@gaco.com
Website: www.gaco.com

1.4 EMERGENCY TELEPHONE NUMBER

For Chemical Emergency
 Spill, Leak, Fire, Exposure, or Incident
 Within USA and Canada: 1-800-424-9300
 Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class:

HAZARD CLASSIFICATION	CATEGORY
Flammable Liquids	2
Eye Damage/Irritation	1

2.2 LABEL ELEMENTS

Hazard pictogram: GHS02, GHS05



SAFETY DATA SHEET

Signal word: Danger

Hazard statement: Highly flammable liquid and vapor
Causes serious eye damage

Prevention: Keep away from heat, hot surfaces/sparks/open flames/hot surfaces. -No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/eye protection/face protection.

Response: If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide (CO2) to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Main symptoms: Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Hazards not otherwise specified: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

36 % of the mixture consists of ingredient(s) of unknown acute toxicity

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Material	CAS No.	Weight %*
Nepheline syenite - various grades	37244-86-5	10-30%
Aluminium hydroxide	21645-51-2	10-30%
Xylene (mixed isomers)	1330-20-7	5-10%
Titanium dioxide (dust)	13463-67-7	5-10%
Zinc borate	138265-88-0	3-7%
Methyl isobutyl ketone	108-10-1	3-7%
cyclohex-1,4-ylenedimethanol	105-08-8	1-5%
Ethylbenzene	100-41-4	1-5%
Butanone	78-93-3	1-5%
Silicon dioxide (dust)	7631-86-9	1-5%

*The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST-AID MEASURES

SAFETY DATA SHEET

4.1 DESCRIPTION OF THE FIRST AID MEASURES

General information:	Ensure that medical personnel are aware of the materials(s) involved, and take precautions to protect themselves.
Inhalation:	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact:	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion:	Rinse mouth. Get medical attention if symptoms occur.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to physicians:	Treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes that do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.
Specific treatments:	In case of accident or if you feel unwell, seek medical advice (show the label or SDS where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

General hazards:	Highly flammable liquid and vapor.
Suitable extinguishing media:	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2)
Unsuitable extinguishing media:	Do not use water jet as an extinguisher as this will spread the fire.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Specific hazards:	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Products of combustion:	May include, and are not limited to: oxides of carbon.

5.3 Special protective equipment and precautions for fire-fighters (PPE)

Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire-fighting procedures:	In case of fire and/or explosion, do not breathe fumes. Move containers from fire area if you can do it without risk.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing

during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

- Methods for containment:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning-up:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see Section 13 of the SDS.
- Large spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
- Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Never return spills to original containers for re-use.
- Environmental precautions:** Avoid discharge into drains, water courses or onto the ground.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Precautions for Safe handling:** Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
- General hygiene advice:** Ensure that medical personnel are aware of the materials(s) involved, and take precautions to protect themselves.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Safe storage:** Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep container tightly closed. Store in a cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
- Specific use:** Architectural Coating and Waterproofing
- Technical measures:** Vapors may form explosive mixtures with air. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment.
- Incompatible materials:** None known, avoid strong oxidizing agents.
- Safe packaging material:** Keep in original container.
- Precautions:** Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges.
- Safe handling advice:** Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke.

Suitable storage conditions:	Take precautionary measures against static discharges. Use personal protection recommended in Section 8 of the SDS. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.
Handling-technical measures:	Use non-sparking tools and explosion-proof equipment. All equipment used when handling this product must be grounded.
Local and general ventilation:	Provide adequate ventilation.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 CONTROL PARAMETERS**

Control parameters: Follow standard monitoring procedures.

Exposure limits:**Nepheline syenite - various grades**

OSHA:
PEL: 5 mg/m³ TQA resp
NIOSH: None

Xylene (mixed isomers)

OSHA:
PEL-TWA ppm: 100
PEL-TWA mg/m³: 435
NIOSH:
REL-TWA ppm: 100
REL-TWA mg/m³: 435
REL-STEL ppm: 150
REL-STEL mg/m³: 655
IDLH ppm: 900

Titanium dioxide (dust)

OSHA:
PEL[†]: TWA 15 mg/m³
NIOSH:
REL: Ca See Appendix A

No significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints

Zinc borate

OSHA:
PEL: 10 mg/m³
PEL (total dust): 15 mg/m³
PEL (Respirable dust): 5 mg/m³
ACGIH: TLV: 10 mg/m³ Cal

Methyl isobutyl ketone

OSHA:
PEL-TWA ppm: 100
PEL-TWA mg/m³: 410
NIOSH:
REL-TWA ppm: 50
REL-TWA mg/m³: 205

REL-STEL ppm: 75
REL-STEL mg/m³: 300
IDLH ppm: 500
ACGIH TWA 20
ACGIH STEL 75

Ethylbenzene

OSHA:
PEL †: TWA 100 ppm (435 mg/m³)
NIOSH:
REL: TWA 100 ppm (435 mg/m³)
ST 125 ppm (545 mg/m³)

Butanone

OSHA:
PEL-TWA ppm: 200
PEL-TWA mg/m³: 590
NIOSH:
REL-TWA ppm: 200
REL-TWA mg/m³: 590
REL-STEL ppm: 300
REL-STEL mg/m³: 885
IDLH ppm: 3000

Silicon dioxide (dust)

OSHA:
PEL †: TWA 20 mppcf (80 mg/m³/%SiO₂) See Appendix C (Mineral Dusts)
NIOSH:
REL: TWA 6 mg/m³

No significant exposure to primary particles of silicon dioxide is thought to occur during the use of products in which silicon dioxide is bound to other materials, such as in paints.

8.2 EXPOSURE CONTROLS**Engineering measures to reduce exposure:**

Explosion-proof general and local exhaust ventilation.

8.3 INDIVIDUAL PROTECTIVE MEASURES

General: Use personal protective equipment as required.
Eye protection: Wear safety glasses with side shields (or goggles) and a face shield.
Hand protection: Wear protective gloves.
Respiratory protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Skin and body protection: Wear suitable protective clothing.
Hygiene measures: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls: Environmental manager must be informed of all major releases.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous light brown liquid
Color:	ADOBE
Form:	Liquid
Odor:	Strong Solvent
Odor Threshold:	Not applicable
Physical State:	Liquid
pH (at 20°C):	Not applicable
Melting Point/Freezing Point:	Not applicable
Initial Boiling Point and Boiling Range:	Not applicable
Flash Point:	60°F/15.56°C
Evaporation Rate:	Not applicable
Flammability (solid, gaseous):	Highly flammable liquid and vapor.
Lower Flammability/Explosive Limit:	Not applicable
Upper Flammability/Explosive Limit:	Not applicable
Vapor Pressure (mm Hg @38°C):	Not applicable
Vapor Density:	Not applicable
Density (lb/gal):	14.16
Relative Density/Specific Gravity:	1.70
Solubility in water/miscibility:	Not applicable
Partition coefficient: n-octanol/water:	Not applicable
Auto-ignition Temperature:	Not applicable
Decomposition Temperature:	Not applicable
Viscosity (at 25°C) g/L:	<140 gku
Oxidizing Properties:	Not applicable
Explosive Properties:	Not applicable
VOC:	<250 g/L (<2.086 lb/gal)
Solvent content - Organic:	Not applicable
Solvent content - Water:	Not applicable
Solvent content - Solids:	83.71%
Other information:	Not applicable
Incompatibilities:	None known, avoid strong oxidizing agents.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2 CHEMICAL STABILITY	
Chemical stability:	Material is stable under normal conditions.
Materials to avoid:	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.3 POSSIBILITY OF HAZARDOUS REACTIONS	
Hazardous reactions:	No dangerous reaction known under conditions of normal use.
10.4 CONDITIONS TO AVOID	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

10.5 INCOMPATIBLE MATERIALS None known, avoid strong oxidizing agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous decomposition products: No hazardous decomposition products are known.

Hazardous polymerization: Does not occur.

Other information: Not applicable.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Acute toxicity: Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Likely routes of exposure: Skin contact. Eye contact. Inhalation.

Eye: Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Skin: No adverse effects due to skin contact are expected. Prolonged skin contact may cause dryness, redness, or cracking.

Ingestion: Not an expected route of exposure. Expected to be a low ingestion hazard.

Inhalation: Not an expected route of exposure. No adverse effects due to inhalation are expected.

LD50/LC50 values relevant to this classification:

Aluminium hydroxide

Oral rat LD50 > 2000 mg/kg bw
Oral rat LD50 > 15900 mg/kg bw
Oral rat LD50 > 10000 mg/kg bw
Inhal rat LC50 > 2.3 mg/L air 4hr
Inhal rat LC50 > 0.888 mg/L air (no deaths) 4hr
Inhal rat LC50 7.6 mg/L air 1hr

Xylene (mixed isomers)

Oral rat LD50 3523-4000 mg/kg bw
Oral rat LD50 5251-5627 mg/kg bw
Oral rat LD50 4300 mg/kg bw
Oral rat LD50 8400 mg/kg
Derm rabbit LD50 >5000 ml/kg bw (4200 mg/kg)
Inhal rat LC50 6700 ppm (29000 mg/m3)
Inhal rat LC50 6247 ppm (27124 mg/m3)

Titanium dioxide (dust)

Oral mouse LD50 > 5000 mg/kg bw
Oral rat LD50 > 5000 mg/kg bw
Oral rat LD50 > 2000 mg/kg bw
Oral rat LD50 > 11000 mg/kg bw
Inhal rat LC50 3.43-5.09 mg/L air
Inhal rat LC50 > 3.56 mg/L air
Inhal rat LC50 > 2.28 mg/L air

Methyl isobutyl ketone

Oral rat LD50 2080 mg/kg bw

Inhal rat LC50 8.2 - 16.4 mg/L air 4hr
Derm rat LD50 > 2,000 mg/kg bw

cyclohex-1,4-ylenedimethanol

Oral rat LD50 >2000 mg/kg bw
Oral rat LD50 3200 < 6400 mg/kg bw
Oral mouse LD50 1600 < 3200 mg/kg bw
Oral rat LD50 1600 < 3200 mg/kg bw
Oral guinea pig LD50 800 < 1600 mg/kg bw
Oral rat LD50 800 < 1600 mg/kg bw
Inhal rat LC50 1 ≤ 3 mg/L air 6hr
Inhal rat LC50 > 1.25 mg/L air 6hr
Derm guinea pig LDLo >1000 mg/kg bw
Derm guinea pig LDLo >20 mg/kg bw

Ethylbenzene

Oral rat LD50 3500 mg/kg bw/day
Oral rat LD50 5460 mg/kg bw/day
Inhal mouse LC50 6.2 mg/L air
Inhal rat LC0 > 400 ppm air no deaths
Inhal gp LC50 >3000 ppm air
Inhal mice LC50 > 8000 ppm
Inhal mouse LC50 35.5 mg/L air
Inhal rat LC50 4000 ppm

Butanone

Oral rat LD50 2193 mg/kg bw

Silicon dioxide (dust)

Oral rat LD50 > 5000 mg/kg bw
Oral rat LD50 >10,000 mg/kg bw
Oral rat LD50 > 5620 mg/kg bw
Oral mouse LD50 > 3160 mg/kg bw
Oral rat LD0 > 20000 mg/kg bw
Oral rat LD50 >3300 mg/kg bw
Oral rat LD0 10,000 mg/kg bw
Inhal rat LC0 > 0.69 mg/L air no deaths
Inhal rat LC0 > 0.14mg/L air no deaths
Inhal rat LC0 > 58.8 mg/L air no deaths
Derm rabbit LD50 > 2000 mg/kg bw
Derm rabbit LD50 > 5000 mg/kg bw

Calculated overall chemical acute toxicity values for this formulation:

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
>5 mg/kg (dust and mist)	>2000 mg/kg	>2000 mg/kg

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin corrosion/irritation: Based on available data, this product is not expected to cause skin corrosion or irritation. Prolonged skin contact may cause dryness, redness, or cracking.

Serious eye damage/irritation: Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

SAFETY DATA SHEET

Respiratory sensitization: Based on available data, this product is not expected to cause respiratory sensitization.

Skin sensitization: Based on available data, this product is not expected to cause skin sensitization.

Symptoms and target organs: Causes severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Chronic health effects: No chronic health effects known.

Carcinogenicity: This product is not classified as a carcinogen. Due to the form of the product, exposure to the potentially carcinogenic components is not expected.

Material	OSHA(O)	ACGIH(G)	NTP(N)	IARC(I)
Titanium dioxide (dust)	Not listed	A4	Not listed	2B
Methyl isobutyl ketone	Not listed	A2	Not listed	2B
Ethylbenzene	Not listed	A3	Not listed	2B

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) =Occupational Safety and Health Administration
Ca/Yes = Expected to be carcinogenic
not listed = Not expected to be carcinogenic

ACGIH (G) =American Conference of Governmental Industrial Hygienists
A1 =Confirmed human carcinogen
A2 =Suspected human carcinogen
A3 =Animal carcinogen
A4 =Not classifiable as a human carcinogen
A5 =Not suspected as a human carcinogen
not listed = Not expected to be carcinogenic

NTP (N) =National Toxicology Program
K =Known to be a carcinogen
R = Reasonably anticipated to be a carcinogen
not listed = Not expected to be carcinogenic
IARC (I) =International Agency for Research on Cancer
1 =Carcinogenic to humans
2A =Probably carcinogenic to humans
2B =Possibly carcinogenic to humans
3 =Not classifiable as to its carcinogenicity to humans
4 =Probably not carcinogenic to humans
not listed = Not expected to be carcinogenic

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity: This product is not expected to cause reproductive or developmental effects.

Specific Target Organ Toxicity (STOT):

Single Exposure: Not classified as an STOT - Single Exposure.

Repeated Exposure: Not classified as an STOT - Repeated Exposure.

Aspiration Toxicity: Based on available data, this product is not expected to cause aspiration toxicity.

Other Information: Not applicable.

SECTION 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Ecotoxicity: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity: Toxic to aquatic life.

Chronic toxicity: Toxic to aquatic life with long lasting effects.

Environmental effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

12.2 PERSISTENCE AND DEGRADABILITY

Persistence/biodegradability: The product contains substances which are not expected to be readily biodegradable.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: No data available.

12.4 MOBILITY

Mobility: No data available.

Mobility in soil: No data available.

Mobility in non-soil: No data available.

12.5 OTHER ADVERSE EFFECTS

Ozone layer: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

- Disposal method:** This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
- Contaminated packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Dispose of contents and container in accordance with all local, regional, national and international regulations.
- EU codes:** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
- Residual waste:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
- Disposal instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Waste codes:** D001: Waste Flammable material with a flash point <140°F (<60°C) The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
- Other disposal recommendations:** None

SECTION 14: TRANSPORT INFORMATION

DOT Non-Bulk

UN: UN1263
Proper shipping name: Paint
Hazard class: 3
Packing group: PG II

DOT Bulk

UN: UN1263
Proper shipping name: Paint
Hazard class: 3
Packing group: PG II

IMDG

UN: UN1263
Proper shipping name: Paint
Hazard class: 3
Packing group: PG II

ICAO/IATA

UN: UN1263
Proper shipping name: Paint
Hazard class: 3
Packing group: PG II

Reportable quantity: Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material

SECTION 15: REGULATORY INFORMATION

SAFETY DATA SHEET

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US Federal Regulations:

U.S. OSHA (Occupational Safety and Health Administration) Specifically Regulated Substances (29 CFR 1910.1001-1050)

No components of this product are present at concentration greater than or equal to 0.1% and are identified as a carcinogen or potential carcinogen by OSHA.

SARA/CERCLA reporting requirements:

The following components of this product are found at concentrations greater than or equal to 0.1% and are subject to SARA/CERCLA reporting requirements.

Material	SARA 302 (EHSs) TPQ	SARA 304 EHSs RQ	CERCLA RQ	SARA 313 listed	RCRA CODE	CAA 112(r) TQ
Xylene (mixed isomers)	Not listed	Not listed	100	313	U239	Not listed
Methyl isobutyl ketone	Not listed	Not listed	5,000	313	U161	Not listed
Ethylbenzene	Not listed	Not listed	1,000	313	Not listed	Not listed
Butanone	Not listed	Not listed	5,000	Not listed	U159	Not listed

State Right-to-Know Regulations

The following components of this product are found at concentrations greater than or equal to 0.1%, subject to state Right-to-Know reporting requirements; or are found at any concentration and are listed under California Proposition 65.

Material	California Proposition 65	Massachusetts Right-to-Know	Minnesota Employee Right-to-Know	New Jersey Community Environmental Hazard	New Jersey Right-to-Know Substance	Pennsylvania Right-to-Know	Rhode Island Right-to-Know
Xylene (mixed isomers)	Not listed	Listed	Listed	Not listed	Listed	Listed	Listed
Titanium dioxide (dust)	Not listed	Listed	Listed	Not listed	Listed	Listed	Not listed
Methyl isobutyl ketone	Cancer	Listed	Listed	Not listed	Listed	Listed	Listed
Ethylbenzene	Cancer	Listed	Listed	Listed	Listed	Listed	Listed
Butanone	Not listed	Not listed	Not listed	Not listed	Not listed	Not listed	Listed
Silicon dioxide (dust)	Not listed	Listed	Listed	Not listed	Not listed	Listed	Not listed
Soybean oil, epoxidized	Not listed	Not listed	Not listed	Not listed	Not listed	Listed	Not listed
Iron oxide	Not listed	Listed	Listed	Not listed	Listed	Listed	Not listed
Zirconium dioxide	Not listed	Listed	Not listed	Not listed	Not listed	Not listed	Not listed
Cumene (mixed isomers)	Cancer	Listed	Listed	Not listed	Listed	Listed	Listed
Toluene	Dev	Listed	Listed	Listed	Listed	Listed	Listed
Benzene (trace)	Cancer	Listed	Listed	Listed	Listed	Listed	Listed
Naphthalene (trace)	Cancer	Listed	Listed	Listed	Listed	Listed	Listed
Vinyl chloride (trace)	Cancer	Listed	Listed	Listed	Listed	Listed	Listed
Nickel (trace)	Cancer	Listed	Listed	Listed	Listed	Listed	Listed
Cobalt (trace)	Cancer	Listed	Listed	Not listed	Listed	Listed	Listed

California:

Proposition 65:



WARNING: This product can expose you to Methyl isobutyl ketone Ethylbenzene, Cumene (mixed isomers), Naphthalene, vinyl chloride, Benzene, Nickel, and Cobalt, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Global Inventories:

Notification status:	
US - TSCA	All substances are listed

SAFETY DATA SHEET

Canada -DSL	Not all substances are listed
Canada - NDSL	At least 1 substance is listed
EU - EINECS	Not all substances are listed
EU - ELINCS	No substances are listed
EU - NLP	At least 1 substance is listed
Australia – AICS	Not all substances are listed
China - EICSC	All substances are listed
Japan - ENCS	Not all substances are listed
Korea - KECI	Not all substances are listed
Taiwan - NECI	All substances are listed
New Zealand - NZIoC	Not all substances are listed
Philippine - PICCS	Not all substances are listed

EU - REACH Status:

A registration number is not available for substances in this mixture as the substances are exempted from registration, the annual tonnage does not require a registration or the registration is envisioned for a later registration deadline.

CANADA – WHMIS (Workplace Hazardous Materials Information System) Classification:

B2, D2A, D2B, E



MEXICO:

Hazard Classification: 3-3-0
Carcinogen Status: No data available.

SECTION 16: OTHER INFORMATION

Health:	3
Flammability:	3
Physical:	0

NFPA 704 (National Fire Protection Association) rating:

Health	3
Fire	3
Reactivity	0

Legend:

- DOT US Department of Transportation
- IATA International Air Transport Association
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- ACGIH American Conference of Governmental Industrial Hygienists
- NTP National Toxicology Program
- IARC International Agency for Research on Cancer
- PPE Personal Protective Equipment
- RCRA Resource Conservation and Recovery Act

SAFETY DATA SHEET

CAA	Clean Air Act
SARA	Superfund Amendments and Reauthorization Act
EPCRA	Emergency Planning and Community Right-to-Know Act
WHMIS	Workplace Hazardous Materials Information System
EU	European Union
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
TSCA	US Toxic Substances Control Act (TSCA)
DSL	Canada Domestic Substance List (DSL)
NDSL	Canada Non-Domestic Substance List (NDSL)
EINECS	European Inventory of Existing Commercial Chemical Substances (EINECS)
ELINCS	European List of Notified Chemical Substances (ELINCS)
NLP	European list of No-longer Polymers (NLP)
AICS	Australian Inventory of Chemical Substances (AICS)
EICSC	China Existing Chemical Inventory - IECSC
ENCS	Japanese Existing and New Chemical Substances Inventory(ENCS)
KECI	Korea Existing Chemicals Inventory(KECI)
NECI	Taiwan National Existing Chemical Inventory (NECI)
NZIoC	New Zealand Inventory of Chemicals (NZIoC)
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
HMIS	Hazardous Materials Identification System
NFPA	National Fire Protection Association (NFPA)

Date of preparation: January 15, 2018

Version: 1.0

Revision Date: January 15, 2018

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Gaco Western LLC

End of Safety Data Sheet