

## SAFETY DATA SHEET

### SECTION 1: IDENTIFICATION

#### 1.1 PRODUCT IDENTIFIER

**Product Name:** POLYASPARTIC/POLYUREA HYBRID PEWTER - POLYOL COMPONENT A  
**Product Code:** U6102P, U6102P-1, U6102P-5

#### 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Product Use:** Architectural Coating and Waterproofing  
 Use this product in accordance with all local, regional, national and international regulations.

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Name/Address:** Firestone Building Products  
 200 4th Avenue South  
 Nashville, TN 37201  
 Gaco is a Firestone Building Products brand

**Telephone Number:** 800-331-0196 / **International:** 001-800-331-0196

**Email:** [sds@gaco.com](mailto:sds@gaco.com)

**Website:** [www.gaco.com](http://www.gaco.com)

#### 1.4 EMERGENCY TELEPHONE NUMBER

For Chemical Emergency  
 Spill, Leak, Fire, Exposure, or Incident  
 Within USA and Canada: 1-800-424-9300  
 Outside USA and Canada: +1-703-527-3887 (collect calls accepted)

### SECTION 2: HAZARD(S) IDENTIFICATION

#### 2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class:

HAZARD CLASSIFICATION	CATEGORY
Eye Damage/Irritation	2A
Sensitization - Skin	1
Flammable Liquids	2

#### 2.2 LABEL ELEMENTS

Hazard pictogram: GHS02, GHS07



## SAFETY DATA SHEET

<b>Signal word:</b>	Danger
<b>Hazard statement:</b>	Highly flammable liquid and vapor May cause an allergic skin reaction Causes serious eye irritation
<b>Prevention:</b>	Keep away from heat, hot surfaces/sparks/open flames/hot surfaces. -No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.
<b>Response:</b>	Specific treatment (see Section 8 on this label). In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide (CO2) to extinguish. If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation or a rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Storage:</b>	Store in a well-ventilated place. Keep cool.
<b>Disposal:</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3 ADDITIONAL INFORMATION

<b>Main symptoms:</b>	Prolonged exposure may cause chronic effects. May cause allergic skin reaction. Dermatitis. Rash. Causes skin irritation. May cause redness and pain. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Hazards not otherwise specified:</b>	Harmful to aquatic life with long lasting effects.

37% of the mixture consists of ingredient(s) of unknown acute toxicity

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 MIXTURES

Material	CAS No.	Weight %*
Nepheline syenite - various grades	37244-86-5	15-40%
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	136210-30-5	10-30%
Titanium dioxide (dust)	13463-67-7	10-30%
Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester	136210-32-7	7-13%
Acetone	67-64-1	3-7%
Silicon dioxide (dust)	7631-86-9	1-5%
diethyl fumarate	623-91-6	1-5%

## SAFETY DATA SHEET

Aluminium hydroxide	21645-51-2	1-5%
1,3,3-trimethyl-N-(2-methylpropylidene)-5-[(2-methylpropylidene)amino]cyclohexanemethylamine	54914-37-3	0.1-1.0%

\*The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: FIRST-AID MEASURES

#### 4.1 DESCRIPTION OF THE FIRST AID MEASURES

- General information:** Ensure that medical personnel are aware of the materials(s) involved, and take precautions to protect themselves.
- Inhalation:** Move to fresh air. Call a physician if symptoms develop or persist.
- Skin contact:** Remove contaminated clothing immediately and wash skin with soap and water. Wash contaminated clothing before reuse. In case of eczema or other skin disorders: Seek medical attention and bring along these instructions.
- Eye contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
- Ingestion:** Rinse mouth. Get medical attention if symptoms occur.

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Prolonged exposure may cause chronic effects. May cause allergic skin reaction. Dermatitis. Rash.  
 Causes skin irritation. May cause redness and pain.  
 Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

- Note to physicians:** Treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes that do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.
- Specific treatments:** In case of accident or if you feel unwell, seek medical advice (show the label or SDS where possible).

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1 EXTINGUISHING MEDIA

- General hazards:** Highly flammable liquid and vapor.
- Suitable extinguishing media:** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media:** Do not use water jet as an extinguisher as this will spread the fire.

#### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

- Specific hazards:** Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
- Products of combustion:** May include, and are not limited to: oxides of carbon.

#### 5.3 Special protective equipment and precautions for fire-fighters (PPE)

- Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
- Special fire-fighting procedures:** In case of fire and/or explosion, do not breathe fumes. Move containers from fire area if you can do it without risk.

**SAFETY DATA SHEET**

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

**6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP**

- Methods for containment:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning-up:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see Section 13 of the SDS.
- Large spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Prevent product from entering drains.
- Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  
Never return spills to original containers for re-use.
- Environmental precautions:** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

**SECTION 7: HANDLING AND STORAGE**

**7.1 PRECAUTIONS FOR SAFE HANDLING**

- Precautions for Safe handling:** Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
- General hygiene advice:** Ensure that medical personnel are aware of the materials(s) involved, and take precautions to protect themselves.

**7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES**

- Safe storage:** Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep container tightly closed. Store in a cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
- Specific use:** Architectural Coating and Waterproofing
- Technical measures:** Vapors may form explosive mixtures with air. All equipment used when handling the product must be grounded. Use non-sparking tools and

**SAFETY DATA SHEET**

<b>Incompatible materials:</b>	explosion-proof equipment.
<b>Safe packaging material:</b>	None known, avoid strong oxidizing agents.
<b>Precautions:</b>	Keep in original container.
<b>Safe handling advice:</b>	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges.
<b>Suitable storage conditions:</b>	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges. Use personal protection recommended in Section 8 of the SDS.
<b>Handling-technical measures:</b>	Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.
<b>Local and general ventilation:</b>	Use non-sparking tools and explosion-proof equipment. All equipment used when handling this product must be grounded.
	Provide adequate ventilation.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 CONTROL PARAMETERS**

**Control parameters:** Follow standard monitoring procedures.

**Exposure limits:**

**Nepheline syenite - various grades**

OSHA:  
 PEL: 5 mg/m<sup>3</sup> TQA resp  
 NIOSH: None

**Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediy)]bis-, 1,1',4,4'-tetraethyl ester**

Oral rat LD50 >2000 mg/kg bw  
 Inhal rat LC50 >4.224 mg/L air 4hr  
 Derm rabbit LD50 >2000 mg/kg bw

**Titanium dioxide (dust)**

OSHA:  
 PEL†: TWA 15 mg/m<sup>3</sup>  
 TWA: 15 mg/m<sup>3</sup> total dust  
 (vacated) TWA: 10 mg/m<sup>3</sup> total dust  
 NIOSH:  
 IDLH: 5000 mg/m<sup>3</sup>  
 REL: Ca See Appendix A  
 ACGIH:  
 TWA: 10 mg/m<sup>3</sup>

No significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints

**Acetone**

OSHA:  
 PEL-TWA ppm: 1000  
 PEL-TWA mg/m<sup>3</sup>: 2400  
 NIOSH:  
 REL-TWA ppm: 250  
 REL-TWA mg/m<sup>3</sup>: 590  
 IDLH ppm: 2500

## SAFETY DATA SHEET

IDLH Notes: 10% of LEL

### Silicon dioxide (dust)

OSHA:

PEL†: TWA 20 mppcf (80 mg/m<sup>3</sup>/%SiO<sub>2</sub>) See Appendix C (Mineral Dusts)

NIOSH:

REL: TWA 6 mg/m<sup>3</sup>

No significant exposure to primary particles of silicon dioxide is thought to occur during the use of products in which silicon dioxide is bound to other materials, such as in paints.

### 8.2 EXPOSURE CONTROLS

#### Engineering measures to reduce exposure:

Explosion-proof general and local exhaust ventilation. Eyewash facilities and emergency shower are highly recommended to be available when handling this product.

### 8.3 INDIVIDUAL PROTECTIVE MEASURES

- General:** Eye wash fountain and emergency showers are recommended. Use personal protective equipment as required.
- Eye protection:** Wear safety glasses with side shields (or goggles).
- Hand protection:** Wear appropriate chemical resistant gloves.
- Respiratory protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
- Skin and body protection:** Wear appropriate chemical resistant clothing.
- Hygiene measures:** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
- Thermal hazards:** Wear appropriate thermal protective clothing, when necessary.
- Environmental exposure controls:** Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

- |   |                                    |
|---|------------------------------------|
| <b>Appearance:</b>                              | Viscous pewter liquid              |
| <b>Color:</b>                                   | PEWTER                             |
| <b>Form:</b>                                    | Not applicable                     |
| <b>Odor:</b>                                    | STRONG SOLVENT                     |
| <b>Odor Threshold:</b>                          | Not applicable                     |
| <b>Physical State:</b>                          | Liquid                             |
| <b>pH (at 20°C):</b>                            | Not applicable                     |
| <b>Melting Point/Freezing Point:</b>            | Not applicable                     |
| <b>Initial Boiling Point and Boiling Range:</b> | Not applicable                     |
| <b>Flash Point:</b>                             | -4°F/-20°C                         |
| <b>Evaporation Rate:</b>                        | Not applicable                     |
| <b>Flammability (solid, gaseous):</b>           | Highly flammable liquid and vapor. |
| <b>Lower Flammability/Explosive Limit:</b>      | Not applicable                     |

## SAFETY DATA SHEET

<b>Upper Flammability/Explosive Limit:</b>	Not applicable
<b>Vapor Pressure (mm Hg @38°C):</b>	Not applicable
<b>Vapor Density:</b>	Not applicable
<b>Density (lb/gal):</b>	12.9
<b>Relative Density/Specific Gravity:</b>	1.55
<b>Solubility in water/miscibility:</b>	slightly soluble in water
<b>Partition coefficient: n-octanol/water:</b>	Not applicable
<b>Auto-ignition Temperature:</b>	Not applicable
<b>Decomposition Temperature:</b>	Not applicable
<b>Viscosity (at 77°F) g/L:</b>	75 ku
<b>Oxidizing Properties:</b>	Not applicable
<b>Explosive Properties:</b>	Not applicable
<b>VOC:</b>	<15 g/L (<0.1251 lb/gal)
<b>Solvent content - Organic:</b>	Not applicable
<b>Solvent content - Water:</b>	Not applicable
<b>Solvent content - Solids:</b>	94.25%
<b>Other information:</b>	Not applicable
<b>Incompatibilities:</b>	None known, avoid strong oxidizing agents.

### SECTION 10: STABILITY AND REACTIVITY

- 10.1 REACTIVITY** The product is stable and non-reactive under normal conditions of use, storage and transport.
- 10.2 CHEMICAL STABILITY**
- Chemical stability:** Material is stable under normal conditions.
- Materials to avoid:** The product is stable and non-reactive under normal conditions of use, storage and transport.
- 10.3 POSSIBILITY OF HAZARDOUS REACTIONS**
- Hazardous reactions:** No dangerous reaction known under conditions of normal use.
- 10.4 CONDITIONS TO AVOID** Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
- 10.5 INCOMPATIBLE MATERIALS** None known, avoid strong oxidizing agents.
- 10.6 HAZARDOUS DECOMPOSITION PRODUCTS**
- Hazardous decomposition products:** No hazardous decomposition products are known.
- Hazardous polymerization:** Does not occur.
- Other information:** Not applicable.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

- Acute toxicity:** May cause an allergic skin reaction. Dermatitis. Rash. Causes skin irritation. May cause redness and pain. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
- Likely routes of exposure:** Skin contact. Eye contact. Inhalation.
- Eye:** Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
- Skin:** May cause an allergic skin reaction. Dermatitis. Rash. Causes skin

## SAFETY DATA SHEET

irritation. May cause redness and pain.

**Ingestion:** Not an expected route of exposure. Expected to be a low ingestion hazard.

**Inhalation:** Not an expected route of exposure. No adverse effects due to inhalation are expected.

**LD50/LC50 values relevant to this classification:****tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate**

Oral rat LD50 >2000 mg/kg bw  
Inhal rat/mouse LC50 841 mg/m<sup>3</sup> air 1hr  
Inhal rat LC50 >4224 mg/m<sup>3</sup> air 4hr  
Inhal rat NOAEL 1436 mg/m<sup>3</sup> air 4hr  
Derm rat LD50 >2000 mg/kg bw

**Titanium dioxide (dust)**

Oral mouse LD50 > 5000 mg/kg bw  
Oral rat LD50 > 5000 mg/kg bw  
Oral rat LD50 > 2000 mg/kg bw  
Oral rat LD50 > 11000 mg/kg bw  
Inhal rat LC50 3.43-5.09 mg/L air  
Inhal rat LC50 > 3.56 mg/L air  
Inhal rat LC50 > 2.28 mg/L air  
Inhal rat LC50 > 6.82 mg/L air 4hr

**Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester**

Oral rat LD50 >2000 mg/kg bw  
Inhal rat LC50 >4.224 mg/L air 4hr  
Derm rabbit LD50 >2000 mg/kg bw

**Acetone**

Oral rat LD50 5800 mg/kg bw  
Oral rat LD50 7190 mg/kg bw  
Inhal rat LC50 132 mg/L air 3hr  
Inhal rat LC50 76.0mg/L air 4hr  
Derm guinea pig LD50 7426 mg/kg bw  
Derm rabbit LD50 15,800 mg/kg bw

**Silicon dioxide (dust)**

Oral rat LD50 > 5000 mg/kg bw  
Oral rat LD50 >10,000 mg/kg bw  
Oral rat LD50 > 5620 mg/kg bw  
Oral mouse LD50 > 3160 mg/kg bw  
Oral rat LD50 mg/kg bw  
Oral rat LD0 > 20000 mg/kg bw  
Oral rat LD50 >3300 mg/kg bw  
Oral rat LD0 10,000 mg/kg bw  
Inhal rat LC0 > 0.69 mg/L air no deaths  
Inhal rat LC0 > 0.14mg/L air no deaths  
Inhal rat LC0 > 58.8 mg/L air no deaths  
Derm rabbit LD50 > 2000 mg/kg bw  
Derm rabbit LD50 > 5000 mg/kg bw

**diethyl fumarate**

Oral rat LD50 1780 mg/kg bw  
Oral rat LD50 1300 mg/kg bw  
Inhal rat LC50 >4224 mg/m<sup>3</sup> air 4hr



## SAFETY DATA SHEET

### Aluminium hydroxide

Oral rat LD50 > 2000 mg/kg bw  
 Oral rat LD50 > 15900 mg/kg bw  
 Oral rat LD50 > 10000 mg/kg bw  
 Inhal rat LC50 > 2.3 mg/L air 4hr  
 Inhal rat LC50 > 0.888 mg/L air (no deaths) 4hr  
 Inhal rat LC50 7.6 mg/L air 1hr

Calculated overall chemical acute toxicity values for this formulation:

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
>5 mg/kg (dust and mist)	>2000 mg/kg	>2000 mg/kg

### 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

**Skin corrosion/irritation:** Causes skin irritation. May cause redness and pain.  
**Serious eye damage/irritation:** Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.  
**Respiratory sensitization:** Based on available data, this product is not expected to cause respiratory sensitization.  
**Skin sensitization:** May cause an allergic skin reaction.  
**Symptoms and target organs:** Prolonged exposure may cause chronic effects. May cause allergic skin reaction. Dermatitis. Rash. Causes skin irritation. May cause redness and pain. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.  
**Chronic health effects:** No chronic health effects known.  
**Carcinogenicity:** This product is not classified as a carcinogen. Due to the form of the product, exposure to the potentially carcinogenic components is not expected.

Material	OSHA(O)	ACGIH(G)	NTP(N)	IARC(I)
Titanium dioxide (dust)	Not listed	A4	Not listed	2B

#### SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** -Occupational Safety and Health Administration  
 Ca/Yes = Expected to be carcinogenic  
 not listed = Not expected to be carcinogenic

**NTP (N)** -National Toxicology Program  
 K =Known to be a carcinogen  
 R = Reasonably anticipated to be a carcinogen  
 not listed = Not expected to be carcinogenic

**ACGIH (G)** -American Conference of Governmental Industrial Hygienists  
 A1 =Confirmed human carcinogen  
 A2 =Suspected human carcinogen  
 A3 =Animal carcinogen  
 A4 =Not classifiable as a human carcinogen  
 A5 =Not suspected as a human carcinogen  
 not listed = Not expected to be carcinogenic

**IARC (I)** -International Agency for Research on Cancer  
 1 =Carcinogenic to humans  
 2A =Probably carcinogenic to humans  
 2B =Possibly carcinogenic to humans  
 3 =Not classifiable as to its carcinogenicity to humans  
 4 =Probably not carcinogenic to humans  
 not listed = Not expected to be carcinogenic

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.  
**Reproductive Toxicity:** This product is not expected to cause reproductive or developmental effects.  
**Specific Target Organ Toxicity (STOT):**  
**Single Exposure:** Not classified as an STOT - Single Exposure.  
**Repeated Exposure:** Not classified as an STOT - Repeated Exposure.  
**Aspiration Toxicity:** Based on available data, this product is not expected to cause aspiration toxicity.  
**Other Information:** Not applicable.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 ECOTOXICITY

**Ecotoxicity:** Harmful to aquatic life with long lasting effects.  
**Acute aquatic toxicity:** The product is not classified as acutely environmentally hazardous. However,

## SAFETY DATA SHEET

**Chronic toxicity:** this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.  
**Environmental effects:** Harmful to aquatic life with long lasting effects.  
 An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### 12.2 PERSISTENCE AND DEGRADABILITY

**Persistence/biodegradability:** The product contains substances which are not expected to be readily biodegradable.

### 12.3 BIOACCUMULATIVE POTENTIAL

**Bioaccumulation:** No data available.

### 12.4 MOBILITY

**Mobility:** No data available.  
**Mobility in soil:** No data available.  
**Mobility in non-soil:** No data available.

### 12.5 OTHER ADVERSE EFFECTS

**Ozone layer:** No data available.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 WASTE TREATMENT METHODS

**Disposal method:** This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

**Contaminated packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**EU codes:** The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Residual waste:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Disposal instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Waste codes:** D001: Waste Flammable material with a flash point <140°F (<60°C) The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Other disposal recommendations:** None

## SECTION 14: TRANSPORT INFORMATION

#### DOT Non-Bulk

**UN:** UN1263  
**Proper shipping name:** Paint  
**Hazard class:** 3  
**Packing group:** PG II

#### DOT Bulk

**UN:** UN1263  
**Proper shipping name:** Paint  
**Hazard class:** 3  
**Packing group:** PG II

#### IMDG

## SAFETY DATA SHEET

UN: UN1263  
 Proper shipping name: Paint  
 Hazard class: 3

Packing group: PG II

### ICAO/IATA

UN: UN1263  
 Proper shipping name: Paint  
 Hazard class: 3

Packing group: PG II

**Reportable quantity:** Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material

### SECTION 15: REGULATORY INFORMATION

#### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

##### US Federal Regulations:

##### U.S. OSHA (Occupational Safety and Health Administration) Specifically Regulated Substances (29 CFR 1910.1001-1050)

No components of this product are present at concentration greater than or equal to 0.1% and are identified as a carcinogen or potential carcinogen by OSHA.

##### SARA/CERCLA reporting requirements:

The following components of this product are found at concentrations greater than or equal to 0.1% and are subject to SARA/CERCLA reporting requirements.

Material	SARA 302 (EHSs) TPQ	SARA 304 EHSs RQ	CERCLA RQ	SARA 313 listed	RCRA CODE	CAA 112(r) TQ
Acetone	Not listed	Not listed	5,000	Not listed	U002	Not listed

##### State Right-to-Know Regulations

The following components of this product are found at concentrations greater than or equal to 0.1%, subject to state Right-to-Know reporting requirements; or are found at any concentration and are listed under California Proposition 65.

Material	California Proposition 65	Massachusetts Right-to-Know	Minnesota Employee Right-to-Know	New Jersey Community Environmental Hazard Right-to-Know	New Jersey Right-to-Know Substance	Pennsylvania Right-to-Know	Rhode Island Right-to-Know
Titanium dioxide (dust)	Cancer (airborne, unbound particles of respirable size)	Listed	Listed	Not listed	Listed	Listed	Not listed
Aspartic acid, N,N'-[methylenebis(2-methyl-4,1-cyclohexanediyl)]bis-, 1,1',4,4'-tetraethyl ester	Not listed	Listed	Not listed	Not listed	Listed	Listed	Not listed
Acetone	Not listed	Listed	Listed	Not listed	Listed	Listed	Listed
Silicon dioxide (dust)	Not listed	Listed	Listed	Not listed	Not listed	Listed	Not listed
Zirconium dioxide	Not listed	Listed	Not listed	Not listed	Not listed	Not listed	Not listed
2,6-Dimethylheptan-4-one	Not listed	Listed	Listed	Not listed	Listed	Listed	Not listed

## SAFETY DATA SHEET

**Global Inventories:**

Notification status:	
US - TSCA	All substances are listed
Canada -DSL	All substances are listed
Canada - NDSL	No substances are listed
EU - EINECS	Not all substances are listed
EU - ELINCS	No substances are listed
EU - NLP	No substances are listed
Australia – AICS	Not all substances are listed
China - EICSC	All substances are listed
Japan - ENCS	Not all substances are listed
Korea - KECI	All substances are listed
Taiwan - NECI	All substances are listed
New Zealand - NZIoC	Not all substances are listed
Philippine - PICCS	Not all substances are listed

**EU - REACH Status:**

A registration number is not available for substances in this mixture as the substances are exempted from registration or the annual tonnage does not require a registration.

HAZARD CLASSIFICATION	CATEGORY
Eye Damage/Irritation	2A
Sensitization - Skin	1
Flammable Liquids	2
Hazardous to the Aquatic Environment - Long-Term (Chronic)	3
Hazard	

**CANADA – WHMIS (Workplace Hazardous Materials Information System) Classification (GHS):**

HAZARD CLASSIFICATION	CATEGORY
Eye Damage/Irritation	2A
Sensitization - Skin	1
Flammable Liquids	2
Hazardous to the Aquatic Environment - Long-Term (Chronic)	3
Hazard	

**MEXICO (GHS):**

HAZARD CLASSIFICATION	CATEGORY
Eye Damage/Irritation	2A
Sensitization - Skin	1
Flammable Liquids	2
Hazardous to the Aquatic Environment - Long-Term (Chronic)	3
Hazard	

**Carcinogen Status:** No data available.

**SECTION 16: OTHER INFORMATION**

**HMIS (Hazardous Materials Identification System) rating:**

## SAFETY DATA SHEET

<b>Health:</b>	<b>2*</b>
<b>Flammability:</b>	<b>3</b>
<b>Physical:</b>	<b>0</b>

**NFPA 704 (National Fire Protection Association) rating:**

<b>Health</b>	<b>2</b>
<b>Fire</b>	<b>3</b>
<b>Reactivity</b>	<b>0</b>

**Legend:**

DOT	US Department of Transportation
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
ACGIH	American Conference of Governmental Industrial Hygienists
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
PPE	Personal Protective Equipment
RCRA	Resource Conservation and Recovery Act
CAA	Clean Air Act
SARA	Superfund Amendments and Reauthorization Act
EPCRA	Emergency Planning and Community Right-to-Know Act
WHMIS	Workplace Hazardous Materials Information System
EU	European Union
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
TSCA	US Toxic Substances Control Act (TSCA)
DSL	Canada Domestic Substance List (DSL)
NDSL	Canada Non-Domestic Substance List (NDSL)
EINECS	European Inventory of Existing Commercial Chemical Substances (EINECS)
ELINCS	European List of Notified Chemical Substances (ELINCS)
NLP	European list of No-longer Polymers (NLP)
AICS	Australian Inventory of Chemical Substances (AICS)
EICSC	China Existing Chemical Inventory - IECSC
ENCS	Japanese Existing and New Chemical Substances Inventory(ENCS)
KECI	Korea Existing Chemicals Inventory(KECI)
NECI	Taiwan National Existing Chemical Inventory (NECI)
NZIoC	New Zealand Inventory of Chemicals (NZIoC)
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
HMIS	Hazardous Materials Identification System
NFPA	National Fire Protection Association (NFPA)

**Date of preparation:**

July 12, 2018

**Version:**

1.0

**Revision Date:**

July 12, 2018

**Disclaimer:**

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Prepared by:**

Firestone Building Products  
 200 4th Avenue South  
 Nashville, TN 37201  
 Gaco is a Firestone Building Products brand

**End of Safety Data Sheet**