

## FM Approvals

### GacoFlex S42 Silicone Roof Maintenance Coating Systems

(S4200 White, S4222 Gray, S4229 Dark Gray, S4248 Tan, and S4258 Santa Fe)

Assembly #	Max Slope	Substrate	Surface Prep	Coverage (gal/sq)	Insulation	Thickness (in.)	Coating	Coverage (gal/sq)	Granules	Coverage (lb/sq)	I/Fire	E/Fire	Wind Uplift	Hail
Maintenance	3.00	Existing PVC	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	3.00	Existing CPA	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing Hypalon	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing EPDM	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing TPO	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing Metal	Firestone Single-Ply LVOC (opt)	0.40			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing BUR	A4271 BleedTrap (opt)	1.00			S42	1@2.00	#11 (opt)	40		A		
Maintenance	5.00	Existing Mod Bit	A4271 BleedTrap (opt)	1.00			S42	1@2.00	#11 (opt)	40		A		