



Product Data Sheet (PDS):

GacoRoof™ Colorant
Revised: 11/2022

GACOROOF™ COLORANT

A. PRODUCT DESCRIPTION:

GacoRoof Colorant is a liquid-silicone alternative to premixed GacoRoof Color.

B. RECOMMENDED USE:

Used as a tint base for GacoRoof White

C. LIMITATIONS:

Only use GacoRoof Colorant to tint GacoRoof White

D. PACKAGED PRODUCT DATA:

This product has the following package product data:

PROPERTY	DESCRIPTION / MEASURED VALUE	
COLORS	GT1621 Gray, GT1670 Mojave Tan NOTE: Color will vary according to the amount of colorant added. If using as a top coat, ensure colors are consistent between batches. Intermixing batches is highly recommended. Gaco Western assumes no responsibility for color inconsistency	
THEORETICAL COVERAGE	A maximum of one can of colorant is recommended per 5 gallons of GacoRoof White.	
SOLIDS	GT1621 Weight: 34 ± 1 % Volume: 27 ± 1 %	GT1670 Weight: 64 ± 1 % Volume: 44 ± 1 %
V.O.C	GT1621 560 g/L	GT1670 432 g/L
FLASH POINT	135 °F (57 °C)	
STORAGE STABILITY	Keep container closed and store in a cool dry place.	

E. INSTALLATION INSTRUCTIONS:

This product has the following installation instructions:

INSTALL STEP	INSTRUCTIONS
1. MIXING	Mix the colorant immediately before beginning the project. Shake colorant container thoroughly to mix pigment.
2. APPLICATION	Add GacoRoof Colorant to a 1 gallon or 5-gallon pail of GacoRoof White. Mix thoroughly with a mechanical mixer, scrape the sides of the pail and then mix again.
3. CLEAN UP	Application tools and equipment can be cleaned with GacoFlex Silicone Solvent or 100% Pure Mineral Spirits. DO NOT USE WATER OR RECLAIMED SOLVENTS.

* For specific Safety and Health information please refer to the appropriate Safety Data Sheet that is associated with this product & published on Gaco.com