

# THE BEST & LAST ROOF COATING YOU'LL EVER USE!



- The Last Roof Coating You'll Ever Need
- Withstands Permanent Ponding Water
- Ideal for Flat or Sloped Roofs



## GacoRoof is Excellent for:

- Aged Asphalt\*
- Aged EPDM†
- Aged TPO/CPA†
- Cap Sheet
- Composite
- Concrete
- Fiberglass
- Metal
- Modified Bitumen
- Smooth Built-Up
- Torchdown
- Sprayed Polyurethane Foam
- Most Existing Coatings
- Low-Pitched Roofs
- Flat Roofs
- Mobile Homes

\*Not for use on 3-tab asphalt or architectural shingles.

†May require GacoFlex E5320 2-Part Epoxy Primer/Filler. Verify adhesion with AdhesionTestKit.

<b>White</b> GR1600	<b>Gray</b> GR1628	<b>Green</b> GR1626
<b>Light Tan</b> GR1670	<b>Rustic</b> GR1671	<b>Medium Blue</b> GR1672
<b>Black</b> GR1673	<b>Brown</b> GR1674	<b>Red</b> GR1675

Note: Colors shown are printed representations of product color. Actual color may vary slightly due to surface texture, application technique and lighting conditions.

Turn over to compare for yourself...

# COMPARE FOR YOURSELF



	GacoRoof	Brand X
Can be applied between 32°F - 120°F	YES	NO
Withstands Permanent Ponding Water	YES	NO
Primer/ Basecoat Required	NO	YES
Re-coating Required	NO	YES

- 2 coat application of same product  
*Brand X requires multiple products*
- Withstands permanent ponding water  
*Brand X is 48 hours only*
- Temperature application range  
32°F - 120°F  
*Brand X is 50°F - 90°F*
- 1-12 hour cure time, dry to the touch  
*Brand X is 24-48 hours*
- 1 gallon = 100 sq. ft. per coat  
*Brand X is 1.5 gallons*
- Can be used on flat roofs  
*Brand X requires 1/4" slope*
- Can be rained on after 2 hours  
*Brand X requires no rain, dew or fog within 24-48 hours*

- Permanently flexible  
*Brand X becomes brittle and begins to degrade over time*
- Recoat can be done after cure time  
*Brand X may require 24 hours before re-coat*
- Silicone Roof Coating  
*Brand X sells all acrylic roof coatings*
- Ponding waterproof  
*Brand X is ponding water resistant*
- No polyester mat between coats  
*Brand X requires polyester mat*
- UV resistant  
*Brand X loses mil thickness due to UV exposure*
- 22 mil system  
*Brand X is 48-60 mil*

For more information call 800.331.0196 or reach out to your GacoFlex Local Area Manager at [Gaco.com/representatives](http://Gaco.com/representatives).