



**Product Data Sheet (PDS):**

**GacoFlex™ A17**  
Revised: 03/2024

**GACOFLEX™ A17  
GACOCRETE ACRYLIC RESURFACER**

**A. PRODUCT DESCRIPTION:**

GacoFlex A17 is an acrylic polymer which adds strength, adhesion and toughness to cementitious materials

**B. RECOMMENDED USE:**

A latex modifier for GacoCrete. This is an overlay system that provides a hard durable surface suitable for the application of most GacoFlex coating systems. GacoCrete is effectively used to repair damaged or worn concrete, weathered plywood and to enhance slope to drain.

See Decking & Waterproofing (DWP) application specification “GW-13-GC - GACOFLEX™ A17 GACOCRETE FOR ROLLER APPLICATION OVER CONCRETE/PLYWOOD DECKING”.

**C. PACKAGED PRODUCT DATA:**

<b>PROPERTY</b>	<b>DESCRIPTION</b>
APPEARANCE	White, milky liquid.
PERFORMANCE ADVANTAGES	Cement mortars modified with GacoFlex A-17 exhibit increased tensile and flexural strengths versus unmodified mortars.  When ambiently cured, thin sections dry rapidly and exhibit excellent toughness and good adhesion to old concrete and masonry, brick, wood, metals, and many other surfaces. Mortars modified with GacoFlex A-17 have improved chemical resistance.
COVERAGE	See Decking & Waterproofing (DWP) application specification “GW-13-GC - GACOFLEX™ A17 GACOCRETE FOR ROLLER APPLICATION OVER CONCRETE/PLYWOOD DECKING”.
V.O.C.	Zero V.O.C.
STORAGE STABILITY	One (1) year from date of manufacture in sealed containers. Protect from freezing.
FLASH POINT	N/A
ADHESION	Modified mortars have excellent adhesion to plywood and concrete. See GW-13-GC.  See Decking & Waterproofing (DWP) application specification “GW-13-GC - GACOFLEX™ A17 GACOCRETE FOR ROLLER APPLICATION OVER CONCRETE/PLYWOOD DECKING”

**D. APPLIED PRODUCT DATA:**

<b>PROPERTY</b>	<b>RESULT</b>
SOLIDS CONTENT	46 – 48 %
PH, WHEN PACKED	9.5 – 10.0
SPECIFIC GRAVITY	1.059
DENSITY	8.8 lb / gal (4 kg / 3.8 L)
FREEZE/THAW STABILITY	5 cycles
MINIMUM FILM-FORMATION TEMPERATURE	50 °F (10 °C)

**E. INSTALLATION INSTRUCTIONS:**

See Decking & Waterproofing (DWP) application specification “GW-13-GC - GACOFLEX™ A17 GACOCRETE FOR ROLLER APPLICATION OVER CONCRETE/PLYWOOD DECKING”

*\* For specific Safety and Health information please refer to the appropriate Safety Data Sheet that is associated with this product & published on Gaco.com.*