



Product Data Sheet (PDS):

GacoFlex™ 66B
Revised: 09/2022

GACOFLEX™ 66B
REINFORCING POLYESTER TEXTURE TAPE

A. PRODUCT DESCRIPTION:

Parchment-like texture tape is made of fusion bonded fabric polyester fibers laid in random orientation. It exhibits a high tensile strength, good elongation and a low profile.

B. RECOMMENDED USE:

Plywood joints, concrete construction joints, concrete cracks, and joints between metal, fiberglass or insulation, and combinations of the above substrates in roof, deck and wall specifications. Can also be used for flashing at changes of plane; however, installation into inside corners requires special care.

C. PACKAGED PRODUCT DATA*:

PROPERTY	DESCRIPTION / MEASURED VALUE
COLOR	White
LENGTH	100 yd (91.4 m) / roll
THICKNESS	5 Mills (0.13 mm)
STORAGE	Store in a cool, dry location.

D. APPLIED PRODUCT DATA*:

PROPERTY	DESCRIPTION / MEASURED VALUE		
TENSILE	TRANSVERSE:	400 psi (2.7 MPa)	ASTM D412-68
	LONGITUDINAL:	800 psi (5.5 MPa)	
ELONGATION	60 %		ASTM D412-68
ADHESION**	**Same as that of primer used.		ASTM D903-49
SOLVENT SWELL	No measurable difference observed.		
HEAT SHRINKAGE	None after 6 months at 150°F (66°C).		

E. INSTALLATION INSTRUCTIONS:

INSTALL STEP	INSTRUCTIONS
1. APPLICATION	Refer to Gaco technical document "General Instructions GW-1-2".

* For specific Safety and Health information please refer to the appropriate Safety Data Sheet that is associated with this product.