



**Product Data Sheet (PDS):**

**GacoFlex™ GacoGrip**  
Revised: 08/2022

**GACOFLEX™ GACOGRIP  
TEXTURE GRANULES**

**A. PRODUCT DESCRIPTION:**

Aggregate of walnut shells that are dense, hard and have a low specific gravity.

**B. RECOMMENDED USE:**

Performs as a skid-resistant texture for pedestrian decks.

**C. PACKAGED PRODUCT DATA\*:**

<b>PROPERTY</b>	<b>DESCRIPTION / MEASURED VALUE</b>	
<b>COLOR</b>	Light Brown	
<b>GRANULE SIZE</b>	40 on 60 (0.42 mm on 0.25 mm)	
<b>PACKAGING</b>	12 oz (340 g) canister	
<b>MOISTURE CONTENT</b>	Less than 2 % by weight after processing.	
<b>FLASH POINT</b>	380 °F (193 °C)	Closed Cup
<b>STORAGE</b>	Store in a dry environment.	

**D. APPLIED PRODUCT DATA\*:**

<b>PROPERTY</b>	<b>DESCRIPTION / MEASURED VALUE</b>	
<b>SPECIFIC GRAVITY</b>	1.35	
<b>HARDNESS</b>	3 – 4	MOHS Scale

**E. INSTALLATION INSTRUCTIONS:**

<b>INSTALL STEP</b>	<b>INSTRUCTIONS</b>
<b>1. APPLICATION</b>	Mix one canister of GacoFlex GacoGrip (12 oz (340 g)) with 1 gal (3.8 L) of GacoFlex GacoDeck TopCoat or any other top coat in need of a non-skid surface. Stir thoroughly, dispersing granules throughout the coating. Apply as recommended on the label of GacoFlex GacoDeck TopCoat or other top coat brands. GacoFlex GacoGrip can be combined with paint and other coatings to achieve a textured surface but must be fully encapsulated in the coating; walnut shells should not be left exposed.

\* For specific Safety and Health information please refer to the appropriate Safety Data Sheet that is associated with this product.